

Round Telescopic Packaging Tube with Locking Mechanism:

- telescopic length extension, ratchet mechanism locks in extended position
- square end prevents rolling
- rigid, durable, humidity and oil resistant
- speedy, efficient packing of products
- re-usable
- available with hanging loop

Availability:

- production against min. order. Please inquire.

Packing:

- outers and inners packed separately in individual cartons

Standard Material:

- Polypropylene (PP) transparent
- Polyethylene (PE) colored

Note: Technical modification and availability subject to change without notice.

Dimensions are measured internally.



rose plastic USA, L.L.P.
P.O. Box 698
California, PA 15419-0698, USA
Tel. ++1/724/9388530
Fax ++1/724/9388532
info@rose-plastic.us
www.rose-plastic.us

Ref.	Dia. Inches	Length Inches	Box Qty.
TP 7 050	0.276	1.969 - 3.543	3200
TP 7 075	0.276	2.953 - 4.528	2100
TP 9 040	0.354	1.575 - 2.559	2000
TP 9 065	0.354	2.559 - 4.331	2000
TP 12 050	0.472	1.969 - 3.150	2900
TP 12 080	0.472	3.150 - 4.724	3500
TP 12 120	0.472	4.724 - 7.874	2000
TP 12 200	0.472	7.874 -14.173	2100
TP 14 050	0.551	1.969 - 3.150	2200
TP 14 080	0.551	3.150 - 4.724	2800
TP 14 120	0.551	4.724 - 7.874	1600
TP 14 200	0.551	7.874 -14.173	1500
TP 16 050	0.630	1.969 - 3.150	1700
TP 16 080	0.630	3.150 - 4.724	2000
TP 16 120	0.630	4.724 - 7.874	1200
TP 16 200	0.630	7.874 -14.173	1200
TP 18 050	0.709	1.969 - 3.150	1500
TP 18 080	0.709	3.150 - 4.724	1700
TP 18 120	0.709	4.724 - 7.874	1100
TP 18 200	0.709	7.874 -14.173	1000
TP 20 050	0.787	1.969 - 3.150	1200
TP 20 080	0.787	3.150 - 4.724	1500
TP 20 120	0.787	4.724 - 7.874	1000
TP 20 200	0.787	7.874 -14.173	900

Ref.	Dia. Inches	Length Inches	Box Qty.
TP 22 050	0.866	1.969 - 3.150	1000
TP 22 080	0.866	3.150 - 4.724	1300
TP 22 120	0.866	4.724 - 7.874	800
TP 22 200	0.866	7.874 -14.173	750
TP 24 050	0.945	1.969 - 3.150	1900
TP 24 080	0.945	3.150 - 4.724	1200
TP 24 120	0.945	4.724 - 7.874	800
TP 24 200	0.945	7.874 -14.173	650
TP 26 050	1.024	1.969 - 3.150	1700
TP 26 080	1.024	3.150 - 4.724	850
TP 26 120	1.024	4.724 - 7.874	550
TP 26 200	1.024	7.874 - 9.843	500
TP 28 050	1.102	1.969 - 3.150	1400
TP 28 080	1.102	3.150 - 4.724	800
TP 28 120	1.102	4.724 - 7.874	500
TP 28 200	1.102	7.874 -14.173	450
TP 30 050	1.181	1.969 - 3.150	1200
TP 30 080	1.181	3.150 - 4.724	650
TP 30 120	1.181	4.724 - 7.874	400
TP 30 200	1.181	7.874 -14.173	400
TP 32 050	1.260	1.969 - 3.150	1000
TP 32 080	1.260	3.150 - 4.724	650
TP 32 120	1.260	4.724 - 7.874	400
TP 32 200	1.260	7.874 -14.173	350